



SPECIFICATIONS OF THE DS-770 REAL RUNNER 2-1-2008

FRAME

Steel framing 2.50" x 2.50" square tubing and 2" x 2" square tubing with a wall thickness of .125 wall.

UPHOLSTERY

Dura-foam Sewn and Stitched pads that have 3/4" plywood back with metal threaded inserts. There are the most durable pad type in the industry.

WELDING

Mig .035 wire welded and all surfaces are descaled.

FINISH

All parts are cleaned and sealed then finished in durable black wrinkle powder coating finish that is baked on at 400 degrees.

DIMENSIONS

41" width 67" length 54" height

BEARINGS

Lubricated which requires almost zero maintenance.

UNIT WEIGHT

235 lbs. Shipped totally assembled with the exception of turning the front handlebar grip frame around. This will only require two 3/4" wrenches. No other tools are needed.

MACHINE SPECIFICS

One set of handle grips to secure the exercise position. Right and left foot pedals that lock each foot in proper alignment and position. Mounted on bearings that allow the foot to pivot and rotate in a natural motion. Machine is set up to accept special rubber floor feet to protect floors and stabilize the machine from motion or movement on concrete or carpeted surfaces.

HYDRUALICS

These come with a total lifetime warranty. No questions asked guarantee. They are custom made for this product and have three adjustable levels of resistance. Resistance is created in both extension and flexion.